



TPU P.87
Small size · Low profile
Face down terminal type

- B09 size**
6.3V
150 μ F
- A09 size**
2.5 to 10V
33 to 100 μ F
- S11 size**
2.5 to 6.3V
33 to 68 μ F
- S09 size**
2.5 to 10V
4.7 to 47 μ F

TH P.102 to 103
Guaranteed at 125°C

- D4D size**
2.5 to 6.3V
330 to 680 μ F
- D4 size**
2.5 to 10V
220 to 1,000 μ F
- D3L size**
2.5 to 10V
100 to 470 μ F
- D2 size**
2.5 to 10V
68 to 220 μ F
- D2E size**
2.5 to 6.3V
150 to 330 μ F

TA P.101
High reliability
(For the car electronics)

- D3L size**
2.5 to 10V
220 to 680 μ F
- D2E size**
2.5 to 10V
68 to 470 μ F
- B2 size**
4.0 to 10V
47 to 100 μ F

TQC P.104
High voltage

- D3 size**
16V
100 μ F
- D3L size**
16 to 25V
33 to 68 μ F
- D2 size**
16 to 35V
10 to 68 μ F
- C size**
16 to 25V
10 to 22 μ F
- B2 size**
16 to 25V
5.6 to 15 μ F

The size of each photo is nearly to full scale.